



## Indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories

### TYPE III - OTHER PROJECT ACTIVITIES

All the approved small-scale methodologies, general guidance to the methodologies, information on additionality and abbreviations can be found at:

<http://edm.unfccc.int/methodologies/SSCmethodologies/approved.html> Project participants shall take into account the general guidance to the methodologies, information on additionality, abbreviations and general guidance on leakage provided at <http://edm.unfccc.int/methodologies/SSCmethodologies/approved.html>.

### III.F. Avoidance of methane production from decay of biomass through composting

#### Technology/measure

1. This project category comprises measures to avoid the production of methane from biomass or other organic matter that would have otherwise been left to decay anaerobically in a solid waste disposal site without methane recovery. Due to the project activity, decay is prevented through aerobic treatment by composting and proper soil application of the compost. The project activity does not recover or combust methane (unlike AMS III.G), and does not undertake controlled combustion of the waste (unlike AMS III E). Measures shall both reduce anthropogenic emissions by sources, and directly emit less than 15 kilo tonnes of carbon dioxide equivalent annually.

2. This category is also applicable is methodology may also be applied in case of project activities with for co-composting wastewater and solid biomass waste, where wastewater would otherwise have been treated in an anaerobic wastewater treatment system without methane recovery. The wastewater in the project scenario is used as a source of moisture and/or nutrients to the composting process e.g. composting of empty fruit bunches (EFB), a residue from palm oil production, with the addition of palm oil mill effluent (POME) which is the wastewater co produced from palm oil production. when such wastewater would otherwise be handled in an anaerobic system without methane recovery

3. This category is applicable for project activities resulting in annual emission reductions lower than 25,000 ton CO<sub>2</sub>e. If the emission reduction of a project activity exceeds the reference value of 25,000 ton CO<sub>2</sub>e in any year of the crediting period, the annual emission reduction for that particular year is capped at 25,000 ton CO<sub>2</sub>e.

4. Measures are limited to those that result in emission reductions of less than or equal to 60 kt CO<sub>2</sub> equivalent annually.

#### Boundary

5. The project boundary is the physical, geographical site:

(a) where the solid waste would have been disposed and the methane emission occurs in absence of the proposed project activity,



### Indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories

#### III.F. Avoidance of methane production from biomass decay through composting (cont)

(b) in the case of projects co-composting wastewater, where the co-composting wastewater would have been treated anaerobically in the absence of the project activity, handled and the corresponding methane emission occurs in the absence of the proposed project activity,

(c) where the treatment of biomass through composting takes place,

(d) where the soil application of the produced compost takes place,

(e) and the itineraries between them (a, b, c and d), where the transportation of waste, wastewater or compost occurs.

#### Project Activity **Direct** Emissions

6. Total annual project activity related emissions shall be less than or equal to 15 kilo tonnes of CO<sub>2</sub> equivalent. Project activity emissions consist of:

(a) CO<sub>2</sub> emissions due to incremental distances between

- (i) The collection points of biomass and the composting site as compared to the baseline solid waste disposal site,
- (ii) When applicable, the collection points of wastewater and composting site as compared to baseline wastewater treatment site,
- (iii) Composting site and the soil application sites.

(b) CO<sub>2</sub> emissions on account of fossil fuel based energy used by the project activity facilities, which shall include but not limited to energy used for aeration and/or turning of compost piles/heaps and chopping of biomass for size reduction, screening and where relevant drying of the final compost product. Emission factors for grid electricity or diesel fuel use as the case may be shall be calculated as described in category AMS I.D.

$$PE_y = PE_{y,transp} + PE_{y,power}$$

Where:

PE<sub>y</sub> project activity emissions in the year “y” (tonnes of CO<sub>2</sub> equivalent)  
PE<sub>y,transp</sub> emissions from incremental transportation in the year “y”  
PE<sub>y,power</sub> emissions from electricity or diesel consumption in the year “y”

7. Project activity that use grid electricity for achieving the aeration and/or turning of the heaps during composting or for the incremental transportation of wastewater to the composting facility will estimate and monitor the emission related to the grid electricity with the approach described in category I.D. If the project activity uses fossil fuels, the emissions will be calculated according to the neat calorific value of the fuels consumed, and the IPCC CO<sub>2</sub> emission factor for the fuels, assuming their complete oxidation

8. Project activity emissions from trucks for incremental waste and wastewater collection and compost delivering activities will be estimated and considered as project activity emissions



### Indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories

#### III.F. Avoidance of methane production from biomass decay through composting (cont)

$$PE_{y,transp} = (Q_y/CT_y) * DAF_w * EF_{CO_2} + (Q_{y,comp}/CT_{y,comp}) * DAF_{comp} * EF_{CO_2}$$

Where:

$Q_y$	quantity of waste composted and/or wastewater co-composted in the year “y” (tonnes)
$CT_y$	average truck capacity for waste transportation (tonnes/truck)
$DAF_w$	average incremental distance for solid waste and/or wastewater transportation (km/truck)
$EF_{CO_2}$	$CO_2$ emission factor from fuel use due to transportation (kg $CO_2$ /km, IPCC default values or local values may be used).
$Q_{y,comp}$	quantity of final compost product produced in the year “y” (tonnes)
$CT_{y,comp}$	average truck capacity for final compost product transportation (tonnes/truck)
$DAF_{comp}$	average distance for final compost product transportation (km/truck)

#### Baseline

9. The baseline scenario is the situation where, in the absence of the project activity, biomass and other organic matter are left to decay within the project boundary and methane is emitted to the atmosphere. The baseline emissions are the amount of methane emitted from the decay of the degradable organic carbon in the biomass solid waste composted in the project activity. When wastewater is co-composted, baseline emissions include emissions from wastewater co-composted in the project activity. The yearly Methane Generation Potential for the solid waste is calculated using the first order decay model as described in category AMS III.G. Baseline emissions shall exclude methane emissions that would have to be captured, fuelled or flared to comply with national or local safety requirement or legal regulations.

$$BE_y = BE_{CH_4,SWDS,y} - MD_{y,reg} * GWP_{CH_4} + MEP_{y,ww} * GWP_{CH_4}$$

where:

$BE_{CH_4,SWDS,y}$	yearly methane generation potential of the solid waste composted by the project during the years “x” from the beginning of the project activity (x=1) up to the year “y” estimated as described in AMS III.G (t $CO_2e$ )
$MD_{y,reg}$	amount of methane that would have to be captured and combusted in the year “y” to comply with the prevailing regulations
$MEP_{y,ww}$	methane emission potential in the year “y” of the wastewater. The value of this term is zero if co-composting of wastewater is not included in the project activity.
$CH_4\_GWP$	GWP for $CH_4$ (value of 21 is used)

10. Methane emission potential of co-composted wastewater is estimated as described in category AMS III.H:

$$MEP_{y,ww} = Q_{y,ww} * COD_{y,ww,untreated} * B_{o,ww} * MCF_{ww,treatment} * GWP_{CH_4}$$

Where:

$Q_{y,ww}$	volume of wastewater co-composted in the year “y” ( $m^3$ )
------------	---



### Indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories

#### III.F. Avoidance of methane production from biomass decay through composting (cont)

$COD_{y,ww,untreated}$	chemical oxygen demand of the wastewater in the year “y” (tonnes/m <sup>3</sup> ) <sup>1</sup>
$B_{o,ww}$	methane producing capacity for the wastewater (IPCC default value for domestic wastewater of 0.21 kg CH <sub>4</sub> /kg.COD) <sup>1</sup>
$MCF_{ww,treatment}$	methane correction factor for the wastewater treatment system in the baseline scenario (MCF higher value as per table III.H.1).

$$BE_y = MB_y * GWP_{CH_4} - MD_{y,reg} * GWP_{CH_4}$$

where:

$MB_y$	methane generation potential in the year “y” (tonnes of CH <sub>4</sub> ), estimated as in AMS III G
$MD_{y,reg}$	methane that would be destroyed or removed in the year “y” for safety or to comply with regulation
$CH_4\_GWP$	GWP for CH <sub>4</sub> (value of 21 is used for the first commitment period)

#### Leakage

11. If the composting technology is the equipment transferred from another activity or if the existing equipment is transferred to another activity, leakage effects are to be considered.

#### Monitoring

12. The emission reduction achieved by the project activity will be measured as the difference between the baseline emission and the sum of the project emission and leakage.

$$ER_y = BE_y - (PE_y + Leakage_y)$$

Where:

$ER_y$  Emission reduction in the year “y” (tCO<sub>2</sub>e)

13. The following parameters shall be monitored and recorded annually during the crediting period:

- Quantity of waste composted ( $Q_{y,comp}$ ) and its composition through representative sampling,
- When project activity includes co-composting of wastewater, the volume of co-composted wastewater ( $Q_{y,ww}$ ) and its COD content through representative sampling,
- When project activity includes co-composting of wastewater, the volume of run-off water<sup>2</sup> from the composting site ( $Q_{ww,runoff}$ ) and its COD content through representative sampling. The methane emission potential of the run-off water is calculated as described in paragraph 9 above and will be subtracted from baseline methane emissions from the wastewater co-composted by the project activity.

<sup>1</sup> The IPCC default value of 0.25 kg CH<sub>4</sub>/kg COD was corrected to take into account the uncertainties. For domestic waste water, a COD based value of  $B_{o,ww}$  can be converted to BOD<sub>5</sub> based value by dividing it by 2.4 i.e. a default value of 0.504 kg CH<sub>4</sub>/kg BOD can be used.

<sup>2</sup> Consisting of the wastewater applied in excess (i.e. moisture over and above the field capacity of the biomass being composted) and rainwater in the case of unroofed sites.



### Indicative simplified baseline and monitoring methodologies for selected small-scale CDM project activity categories

#### III.F. Avoidance of methane production from biomass decay through composting (cont)

- Parameters related to project emissions ( $PE_y$ ) described above such as  $CT_y$ ,  $DAF_w$ ,  $CT_{y,comp}$ , energy used for aeration, turning of compost piles, pre-processing of the biomass (e.g. size reduction, screening) and where relevant drying of the final compost product.

14. The amount of waste composted in the project activity in each year ( $Q_y$ ) will be measured and recorded, as well as its composition through representative sampling, to provide information for estimating the baseline emissions. The total quantity of waste ( $Q_y$ ) and compost ( $Q_{y,comp}$ ) processed each year, and the average truck capacity ( $CT_y$ ) will be measured to provide information for estimating the project activity emissions through transportation. The power consumption will be measured and registered. The monitoring will also record the distance for which the waste is transported in the baseline and the project scenario including transport of the compost to the soil application sites.

15. The operation of the composting facilities will be documented in a quality control program, monitoring the conditions and procedures that ensure the aerobic condition of the waste during the composting process.

16. Soil application of the compost in agriculture or related activities will be monitored. This includes documenting the sales or delivery of the compost final product. It shall also include an in situ verification of the proper soil application of the compost to ensure aerobic conditions for further decay. Such verification shall be done at representative sample of user sites.

17. The project participants shall demonstrate annually, through the assessment of common practices at proximate waste disposal sites, that the amount of waste composted in the project activity facilities would have been disposed in a solid waste disposal site without methane recovery in the absence of the project activity. When project activity includes co-composting of wastewater demonstrate that wastewater would have been treated in an anaerobic system without methane recovery in the absence of the project activity.